

8919

Double Coated PE Foam Tape

General Description:

0,8 mm white, closed cells, medium density PE foam coated with a high performance acrylic adhesive system and protected by siliconized paper release liner. Designed for general purpose mounting, assembling of displays, hooks, cable clips, plastic profiles, emblems.

Product Features And Applications:

- High initial tack and shear strength
- Excellent UV and ageing resistance
- Good adhesion to a variety of smooth and rough substrates
- Mounting of plastic parts in the automotive industry
- Mounting of decorative profiles, furniture trims, electrical conduits
- Mounting of nameplates, emblems and plastic profiles in the building & construction industry



Technical data sheet

PRODUCT TYPE	Double coated
BACKING TYPE	PE FOAM
ADHESIVE TYPE	Modified acrylic
COLOR	White
LINER TYPE	Bi-siliconized paper
LINER COLOR	White
BACKING THICKNESS	800 µm
TOTAL THICKNESS	900 µm
PEEL ADHESION AT 90° ON STEEL	9.00 N/cm
ROLLING BALL TACK	< 10 cm
STATIC SHEAR	≥ 168 hrs
SHORT TIME TEMPERATURE RESISTANCE	120 °C
TEMPERATURE RESISTANCE	-30 °C-90 °C
SHELF LIFE	12 months
NOTE 1	Also available in spool wound rolls
NOTE 2	Peel adhesion based on internal method
STANDARD LENGTH	66 m
STANDARD WIDTH	1220 mm

International Harmonized Test Methods: ASTM D-1000, PSTC, EN 60454-2

All statements and information listed above regarding this product are typical values for general guidance, these data have not to be intended as conformity specification. These suggestions are based on tests we believe reliable, but are not guaranteed for accuracy and completeness. The user must test, evaluate and validate this product before the use, assuming risks and liability of such use. This document may be revised without prior notice, the user who downloaded it will automatically be informed of any future revisions. Suggested storage temperature is between 10°C and 30°C with 50% relative humidity.