



Safety Data Sheet

Copyright,2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-7905-5	Version number:	1.04
Revision date:	16/08/2022	Supersedes date:	25/07/2022
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear Off White

Product Identification Numbers

UU-0114-7504-1 UU-0114-7505-8 UU-0116-1335-1

7100261679 7100261739 4100059983

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

07-7184-0, 42-7068-2

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Contains:

Nitric acid, calcium salt, tetrahydrate; bis-[4-(2,3-epoxipropoxy)phenyl]propane; 2,4,6-tris(dimethylaminomethyl)phenol; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P273	Avoid release to the environment.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P260A Do not breathe vapours.
P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit: Component document group number(s) information was modified.
Label: CLP Ingredients - kit components information was modified.



Safety Data Sheet

Copyright,2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	42-7068-2	Version number:	1.02
Revision date:	11/10/2022	Supersedes date:	25/07/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	65 - 75
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9		7 - 13

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

25% of the mixture consists of components of unknown acute oral toxicity.

Contains 52% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	65 - 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Acrylic copolymer	Trade Secret	< 15	Substance not classified as hazardous
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	(CAS-No.) 29407-84-9	7 - 13	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
2,6-Di-tert-butyl-p-cresol	(CAS-No.) 128-37-0 (EC-No.) 204-881-4 (REACH-No.) 01-2119555270-46,01-2119565113-46	< 0.3	Aquatic Chronic 1, H410,M=1 Aquatic Acute 1, H400,M=1
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01-2119513212-58	< 2	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	< 2	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2,6-Di-tert-butyl-p-cresol	128-37-0	UK HSC	TWA:10 mg/m ³	
Silicon dioxide	67762-90-7	UK HSC	TWA(as respirable dust):2.4 mg/m ³ ;TWA(as inhalable dust):6 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Yellow
Odor	Epoxy
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	>=200 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Flash point	Flash point > 93 °C (200 °F) [<i>Test Method: Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>Not applicable.</i>
Density	1.15 g/cm ³
Relative density	1.11 - 1.15
Relative Vapor Density	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds
Evaporation rate
Percent volatile

No data available.
Not applicable.
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Acrylic copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylic copolymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Ingestion	similar compounds	LD50 estimated to be > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
2,6-Di-tert-butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-Di-tert-butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Rabbit	Mild irritant
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
2,6-Di-tert-butyl-p-cresol	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Rabbit	Moderate irritant
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Severe irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
2,6-Di-tert-butyl-p-cresol	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Human and animal	Sensitising
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Professional judgement	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
2,6-Di-tert-butyl-p-cresol	Human	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxypropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,6-Di-tert-butyl-p-cresol	In Vitro	Not mutagenic
2,6-Di-tert-butyl-p-cresol	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
2,6-Di-tert-butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-Di-tert-butyl-p-cresol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-Di-tert-butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-Di-tert-butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25	2 generation

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

					mg/kg/day	
2,6-Di-tert-butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	EC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Acrylic copolymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Phenol,4,4'-(1-methylethylidene)bis-polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2,6-Di-tert-butyl-p-cresol	128-37-0	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC50	>0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	48 hours	EC50	0.48 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

2,6-Di-tert-butyl-p-cresol	128-37-0	Green algae	Experimental	72 hours	EC10	0.4 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Medaka	Experimental	42 days	NOEC	0.053 mg/l
2,6-Di-tert-butyl-p-cresol	128-37-0	Water flea	Experimental	21 days	NOEC	0.023 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	ErC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Invertebrate	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	100 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Acrylic copolymer	Trade Secret	Data not available - insufficient	N/A	N/A	N/A	N/A
Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	Data not available - insufficient	N/A	N/A	N/A	N/A
2,6-Di-tert-butyl-p-cresol	128-37-0	Data not available - insufficient	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 %removal of DOC	EC C.4.A. DOC Die-Away Test
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available - insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	
Acrylic copolymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M Scotch-Weld(tm) Epoxy Structural adhesive DP-410 Clear

Phenol,4,4'-(1-methylethylidene)bis-,polymer with (butoxymethyl)oxirane and (chloromethyl)oxirane	29407-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,6-Di-tert-butyl-p-cresol	128-37-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	1277	OECD305-Bioconcentration
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Experimental Bioconcentration		Log Kow	0.5	Episuite™
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(EPOXY RESIN)

14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2,6-Di-tert-butyl-p-cresol	128-37-0	Gr. 3: Not classifiable	International Agency for Research on Cancer
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 03: SCL table information was modified.

Section 5: Fire - Advice for fire fighters information information was modified.

Section 5: Fire - Extinguishing media information information was modified.

Section 5: Fire - Special hazards information information was modified.

Section 6: Accidental release clean-up information information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 7: Precautions safe handling information information was modified.

Section 9: Flash point information information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright,2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	07-7184-0	Version number:	17.01
Revision date:	11/10/2022	Supersedes date:	25/03/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	40 - 70
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	10 - 30
Nitric acid, calcium salt, tetrahydrate	13477-34-4	233-332-1	7 - 13
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	7 - 13

HAZARD STATEMENTS:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260A	Do not breathe vapours.
P280B	Wear protective gloves and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P260A Do not breathe vapours.
 P280B Wear protective gloves and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTRE or doctor/physician.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

1% of the mixture consists of components of unknown acute dermal toxicity.

Contains 1% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.
 This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2 (REACH-No.) 01-2119963377-26	40 - 70	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1 (REACH-No.) 01-2119495093-35	7 - 13	Acute Tox. 4, H302 Eye Dam. 1, H318
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (REACH-No.) 01-2119560597-27	7 - 13	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	< 5	Acute Tox. 4, H302 Skin Corr. 1C, H314

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO₂ (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Amine compounds.
Carbon monoxide
Carbon dioxide.
Hydrogen Chloride

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

Oxides of nitrogen.

During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d

3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	59 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Local effects	13 mg/m ³
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Systemic effects	176 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater	0.22 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater sediments	0.809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Intermittent releases to water	2.2 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water	0.022 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water sediments	0.0809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Sewage Treatment Plant	125 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.7	=>8 hours
Neoprene.	0.5	=>8 hours
Nitrile rubber.	0.4	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Thixotropic paste
Colour	Off-White
Odor	Amine
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	Not applicable.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	>=100 °C [Test Method:Closed Cup]

Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>Not applicable.</i>
Density	1.09 - 1.12 g/ml
Relative density	1.09 - 1.12 [Ref Std: WATER=1]
Relative Vapor Density	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>Not applicable.</i>
Percent volatile	<=1 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar compounds	LD50 > 2,000 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Mild irritant
Nitric acid, calcium salt, tetrahydrate	similar compounds	No significant irritation

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Moderate irritant
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
Bis[(dimethylamino)methyl]phenol	similar compounds	Corrosive

Skin Sensitisation

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professional judgement	Sensitising
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human and animal	Sensitising
Nitric acid, calcium salt, tetrahydrate	similar compounds	Not classified
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compounds	NOAEL 1,500 mg/kg/day	prematuring into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compounds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compounds	NOAEL 1,500 mg/kg/day	prematuring into lactation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemia	Causes damage to organs	Human	NOAEL Not available	environmental exposure
2,4,6-tris(dimethylaminomethyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

Nitric acid, calcium salt, tetrahydrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	similar compounds	NOAEL 1,500 mg/kg/day	28 days
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

opane						
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Green algae	Experimental	72 hours	EC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Bis[(dimethylamino)methyl]phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THC O2 evolution	Catalogic™

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	
bis-[4-(2,3-epoxipropoxy)phenyl]propopane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	

3M™Epoxy Structural Adhesive Scotch-Weld™ DP410 : Part A

ne						
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

ADR: UN3263; Corrosive Solid, Basic, Organic, N.O.S. (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II; (E); C8.
IMDG: UN3263; Corrosive Solid, Basic, Organic, N.O.S. (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II; EMS: FA, SB.

IATA: UN3263; Corrosive Solid, Basic, Organic, N.O.S. (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

bis-[4-(2,3-epoxypropoxy)phenyl]propane

CAS Nbr

1675-54-3

Classification

Gr. 3: Not classifiable

Regulation

International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions

on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Section 2: <125ml Precautionary - Prevention information was modified.

Label: CLP Precautionary - Prevention information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was modified.

Section 15: Restrictions on manufacture ingredients information information was added.

Annex

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Transfer
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Transfer of substance/mixture with dedicated engineering controls.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Processing Temperature:: 20 degree Celsius;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
Processes, tasks and activities covered	Application of product through a mixing nozzle
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Processing Temperature:: 20 degree Celsius;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health:

	Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;
Waste management measures	Do not release to waterways or sewers; Incinerate in a permitted hazardous waste incinerator;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk