

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikaflex®-292i

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

|                          |   |   |   |
|--------------------------|---|---|---|
| Hazard pictograms        | : |  |   |
| Signal word              | : | Warning   |   |
| Hazard statements        | : | H317  | May cause an allergic skin reaction.                                  |
| Precautionary statements | : | P101  | If medical advice is needed, have product container or label at hand. |
|                          | : | P102  | Keep out of reach of children.  |
|                          |   | <b>Prevention:</b>  |   |
|                          | : | P261  | Avoid breathing mist or vapours.                                      |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|  |                  |  |
|--|------------------|--|
|  | P280             | Wear protective gloves.  |
|  | <b>Response:</b> |  |
|  | P302 + P352      | IF ON SKIN: Wash with plenty of water.                             |
|  | <b>Disposal:</b> |  |
|  | P501             | Dispose of contents/container in accordance with local regulation. |

### Hazardous components which must be listed on the label:

Hexamethylene-1,6-diisocyanate homopolymer  
Hardener LH (1,6-Hexanedialdimine)  
Hardener LI (Isophoronedialdimine)  
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane  
Pentamethyl piperidylsebacate  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
4,4'-methylenediphenyl diisocyanate  
m-tolylidene diisocyanate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

| Chemical name  | CAS-No.<br>EC-No.<br>Registration number            | Classification  | Concentration<br>(% w/w) |
|--|---|---|--------------------------|
| Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-  | 77703-56-1<br>416-600-4<br>01-0000016345-72-XXXX    | Aquatic Chronic 4;<br>H413  | >= 2,5 - < 5             |
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]   | 13463-67-7<br>236-675-5<br>01-2119489379-17-XXXX    | Carc. 2; H351   | >= 2,5 - < 5             |
| Hexamethylene-1,6-diisocyanate homopolymer<br>Contains:<br>hexamethylene-di-isocyanate <= 0,3 %  | 28182-81-2<br>931-274-8<br>01-2119485796-17-XXXX    | Acute Tox. 4; H332<br>Skin Sens. 1; H317<br>STOT SE 3; H335   | < 1                      |
| Hardener LH (1,6-Hexanedialdimine)   | 613222-52-9<br>479-930-8<br>UK-01-7050478074-6-0001 | Eye Dam. 1; H318<br>Skin Sens. 1B; H317<br>STOT SE 3; H335<br>(Respiratory system)  | < 1                      |
| Hardener LI (Isophoronedialdimine)   | 932742-30-8<br>700-071-4<br>UK-01-4889597125-6-0001 | Skin Sens. 1B; H317<br>Aquatic Chronic 3;<br>H412   | >= 0,25 - < 1            |
| Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane  | 192526-20-8<br>924-669-1<br>01-2120768758-32-XXXX   | Skin Sens. 1A; H317<br>Aquatic Chronic 4;<br>H413   | >= 0,1 - < 0,25          |
| Pentamethyl piperidylsebacate<br>Contains:<br>bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate<br>methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | 1065336-91-5<br>915-687-0<br>01-2119491304-40-XXXX  | Skin Sens. 1A; H317<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><br>M-Factor (Acute aquatic toxicity): 1<br>M-Factor (Chronic aquatic toxicity): 1 | >= 0,1 - < 0,25          |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021

Version 9.0

Print Date 24.08.2021

Revision Date: 05.07.2021

|   |   |   |                   |
|---|---|---|-------------------|
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9<br>223-861-6<br>01-2119490408-31-XXXX | Acute Tox. 1; H330<br>Skin Irrit. 2; H315<br>Eye Irrit. 2; H319<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>(Respiratory system)<br>Aquatic Chronic 2;<br>H411<br><hr/> specific concentration limit<br>Resp. Sens. 1; H334<br>>= 0,5 %<br>Skin Sens. 1; H317<br>>= 0,5 %<br>Resp. Sens. 1; H334<br>>= 0,5 %<br>Skin Sens. 1; H317<br>>= 0,5 % | >= 0,025 - < 0,25 |
|---|---|---|-------------------|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021

Version 9.0

Print Date 24.08.2021

Revision Date: 05.07.2021

|  |   |   |                 |
|--|---|---|-----------------|
| <p>4,4'-methylenediphenyl diisocyanate</p> | <p>101-68-8<br/>202-966-0<br/>01-2119457014-47-XXXX</p> | <p>Acute Tox. 4; H332<br/>Skin Irrit. 2; H315<br/>Eye Irrit. 2; H319<br/>Resp. Sens. 1; H334<br/>Skin Sens. 1; H317<br/>Carc. 2; H351<br/>STOT SE 3; H335<br/>(Respiratory system)<br/>STOT RE 2; H373</p> <hr/> <p>specific concentration limit<br/>Eye Irrit. 2; H319<br/>&gt;= 5 %<br/>STOT SE 3; H335<br/>&gt;= 5 %<br/>Skin Irrit. 2; H315<br/>&gt;= 5 %<br/>Resp. Sens. 1; H334<br/>&gt;= 0,1 %<br/>STOT RE 2; H319<br/>&gt;= 5 %<br/>STOT SE 3; H335<br/>&gt;= 5 %<br/>Skin Irrit. 2; H315<br/>&gt;= 5 %<br/>Resp. Sens. 1; H334<br/>&gt;= 0,1 %</p> <hr/> <p>Acute toxicity estimate<br/><br/>Acute inhalation toxicity (dust/mist): 1,5 mg/l</p> | <p>&lt; 0,1</p> |
|--|---|---|-----------------|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|                           |  |  |                  |
|---------------------------|--|--|------------------|
| m-tolylidene diisocyanate | 26471-62-5<br>247-722-4<br>01-2119454791-34-XXXX | Carc. 2; H351<br>Acute Tox. 1; H330<br>Eye Irrit. 2; H319<br>STOT SE 3; H335<br>Skin Irrit. 2; H315<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>Aquatic Chronic 3;<br>H412<br><hr/> specific concentration limit<br>Resp. Sens. 1; H334<br>>= 0,1 %<br>Resp. Sens. 1; H334<br>>= 0,1 % | >= 0,025 - < 0,1 |
|---------------------------|--|--|------------------|

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : sensitising effects

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

---

May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components  | CAS-No.    | Value type (Form of exposure) | Control parameters *         | Basis * |
|---|------------|-------------------------------|------------------------------|---------|
| titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]   | 13463-67-7 | TWA (inhalable dust)          | 10 mg/m <sup>3</sup>         | GB EH40 |
|   |            | TWA (Respirable dust)         | 4 mg/m <sup>3</sup>          | GB EH40 |
| Hexamethylene-1,6-diisocyanate homopolymer  | 28182-81-2 | TWA                           | 0,02 mg/m <sup>3</sup> (NCO) | GB EH40 |
| Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) |            |                               |                              |         |



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|   |   |  |         |  |
|---|---|--|---------|--|
|   | <p>can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitizer will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitizers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p> |  |         |  |
|   | STEL  | 0,07 mg/m <sup>3</sup><br>(NCO)        | GB EH40 |  |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9   | TWA<br>0,02 mg/m <sup>3</sup><br>(NCO) | GB EH40 |  |
|   | <p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitizers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitizer will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not</p>   |  |         |  |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|  |            |   |                  |         |
|--|------------|---|------------------|---------|
|  |            | include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages ( <a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a> ) provide further information. |                  |         |
|  |            | STEL  | 0,07 mg/m3 (NCO) | GB EH40 |
| 4,4'-methylenediphenyl diisocyanate                          | 101-68-8   | TWA   | 0,02 mg/m3 (NCO) | GB EH40 |
| Further information: Capable of causing occupational asthma. |            |   |                  |         |
|  |            | STEL  | 0,07 mg/m3 (NCO) | GB EH40 |
| m-tolylidene diisocyanate                                    | 26471-62-5 | TWA   | 0,02 mg/m3 (NCO) | GB EH40 |
|  |            | Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate   |                  |         |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|  |  |                              |         |
|--|--|------------------------------|---------|
|  | standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages ( <a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a> ) provide further information. |                              |         |
|  | STEL   | 0,07 mg/m <sup>3</sup> (NCO) | GB EH40 |

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Biological occupational exposure limits

| Substance name  | CAS-No.    | Control parameters  | Sampling time                        | Basis       |
|---|------------|---|--------------------------------------|-------------|
| Hexamethylene-1,6-diisocyanate homopolymer              | 28182-81-2 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |
| 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 4098-71-9  | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |
| 4,4'-methylenediphenyl diisocyanate                     | 101-68-8   | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |
| m-tolylidene diisocyanate                               | 26471-62-5 | isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine) | At the end of the period of exposure | GB EH40 BAT |

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name   | End Use | Exposure routes | Potential health effects   | Value                 |
|--|---------|-----------------|----------------------------|-----------------------|
| Reaction product of Hexamethylene diisocyanate, oligomers with | Workers | Inhalation      | Long-term systemic effects | 1,7 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|                                 |           |            |                            |           |
|---------------------------------|-----------|------------|----------------------------|-----------|
| Mercaptopropyltri-methoxysilane |           |            |                            |           |
|                                 | Workers   | Dermal     | Long-term systemic effects | 4,7 mg/kg |
|                                 | Consumers | Inhalation | Long-term systemic effects | 0,3 mg/m3 |
|                                 | Consumers | Dermal     | Long-term systemic effects | 1,7 mg/kg |

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name  | Environmental Compartment | Value       |
|---|---------------------------|-------------|
| Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane | Fresh water               | 0,1 mg/l    |
|   | Intermittent use/release  | 1 mg/l      |
|   | Marine water              | 0,01 mg/l   |
|   | Intermittent use/release  | 1 mg/l      |
|   | Fresh water sediment      | 23,28 mg/kg |
|   | Marine sediment           | 2,33 mg/kg  |
|   | Sewage treatment plant    | 100 mg/l    |
|   | Soil                      | 4,58 mg/kg  |

## 8.2 Exposure controls

### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                             |   |
|-----------------------------|---|
| Physical state              | : liquid  |
| Appearance                  | : paste   |
| Colour                      | : various   |
| Odour                       | : odourless   |
| Boiling point/boiling range | : No data available   |
| Flash point                 | : > 101 °C<br>Method: closed cup                                |
| Auto-ignition temperature   | : No data available   |
| pH                          | : Not applicable<br>substance/mixture is non-soluble (in water) |

### Viscosity

|                      |                  |
|----------------------|------------------|
| Viscosity, dynamic   | : Not applicable |
| Viscosity, kinematic | : Not applicable |

### Solubility(ies)

|                  |                                     |
|------------------|-------------------------------------|
| Water solubility | : insoluble                         |
| Vapour pressure  | : 0,01 hPa                          |
| Density          | : ca. 1,3 g/cm <sup>3</sup> (20 °C) |

### 9.2 Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402

##### **Hexamethylene-1,6-diisocyanate homopolymer:**

Acute oral toxicity : LD50 Oral (Rat): > 2.500 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

##### **Hardener LI (Isophoronedialdimine):**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### **Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402

### **Pentamethyl piperidylsebacate:**

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 4.700 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

### **m-tolylidene diisocyanate:**

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Raphidocelis subcapitata (freshwater green alga)): >  
plants 100 mg/l  
Exposure time: 72 h

#### **Hardener LI (Isophoronedialdimine):**



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|   |   |   |
|---|---|---|
| Toxicity to fish                                    | : | LC50 (Fish): 87,2 mg/l<br>Exposure time: 96 h                                   |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia (water flea)): > 100 mg/l<br>Exposure time: 48 h                  |
| Toxicity to algae/aquatic plants                    | : | EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l<br>Exposure time: 72 h |

### Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane:

|   |   |  |
|---|---|--|
| Toxicity to fish                                    | : | LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203           |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202              |
| Toxicity to algae/aquatic plants                    | : | EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l<br>Exposure time: 72 h<br>Method: OECD Test Guideline 201 |

### Pentamethyl piperidylsebacate:

|                                     |   |   |
|-------------------------------------|---|---|
| Toxicity to fish                    | : | LC50 (Fish): 0,97 mg/l<br>Exposure time: 96 h |
| M-Factor (Acute aquatic toxicity)   | : | 1   |
| M-Factor (Chronic aquatic toxicity) | : | 1   |

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

|            |   |   |
|------------|---|---|
| Assessment | : | This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.. |
|------------|---|---|

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number

- ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

---

Country GB 000000607756

18 / 22

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA (Cargo)** : Not regulated as a dangerous good  
**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
(Number on list 74)  
4,4'-methylenediphenyl diisocyanate  
(Number on list 74, 56)  
m-tolylidene diisocyanate (Number on list 74)  
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich  
(Number on list 52)

International Chemical Weapons Convention (CWC) : Not applicable

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

### Schedules of Toxic Chemicals and Precursors

|  |   |   |
|--|---|---|
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).                                      | : | None of the components are listed (=> 0.1 %).   |
| REACH - List of substances subject to authorisation (Annex XIV)  | : | Not applicable  |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer  | : | Not applicable  |
| Regulation (EU) 2019/1021 on persistent organic pollutants (recast)  | : | Not applicable  |
| Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals | : | Not applicable  |
| REACH Information:   | : | All substances contained in our Products are<br>- registered by our upstream suppliers, and/or<br>- registered by us, and/or<br>- excluded from the regulation, and/or<br>- exempted from the registration. |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

|                            |   |   |
|----------------------------|---|---|
| Volatile organic compounds | : | Law on the incentive tax for volatile organic compounds (VOCV)<br>no VOC duties<br><br>Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)<br>Not applicable |
|----------------------------|---|---|

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

|  |   |  |
|--|---|--|
| Health, safety and environmental regulation/legislation specific for the substance or mixture: | : | Environmental Protection Act 1990 & Subsidiary Regulations<br>Health and Safety at Work Act 1974 & Subsidiary Regulations<br>Control of Substances Hazardous to Health Regulations (COSHH)<br>May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments. |
|--|---|--|

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

---

### SECTION 16: Other information

#### Full text of H-Statements

|      |   |
|------|---|
| H315 | : Causes skin irritation.   |
| H317 | : May cause an allergic skin reaction.  |
| H318 | : Causes serious eye damage.  |
| H319 | : Causes serious eye irritation.  |
| H330 | : Fatal if inhaled.   |
| H332 | : Harmful if inhaled.   |
| H334 | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.    |
| H335 | : May cause respiratory irritation.   |
| H351 | : Suspected of causing cancer.  |
| H351 | : Suspected of causing cancer if inhaled.                                       |
| H373 | : May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400 | : Very toxic to aquatic life.   |
| H410 | : Very toxic to aquatic life with long lasting effects.                         |
| H411 | : Toxic to aquatic life with long lasting effects.                              |
| H412 | : Harmful to aquatic life with long lasting effects.                            |
| H413 | : May cause long lasting harmful effects to aquatic life.                       |

#### Full text of other abbreviations

|                 |  |
|-----------------|--|
| Acute Tox.      | : Acute toxicity   |
| Aquatic Acute   | : Short-term (acute) aquatic hazard  |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard   |
| Carc.           | : Carcinogenicity  |
| Eye Dam.        | : Serious eye damage   |
| Eye Irrit.      | : Eye irritation   |
| Resp. Sens.     | : Respiratory sensitisation  |
| Skin Irrit.     | : Skin irritation  |
| Skin Sens.      | : Skin sensitisation   |
| STOT RE         | : Specific target organ toxicity - repeated exposure   |
| STOT SE         | : Specific target organ toxicity - single exposure   |
| GB EH40         | : UK. EH40 WEL - Workplace Exposure Limits   |
| GB EH40 BAT     | : UK. Biological monitoring guidance values  |
| GB EH40 / TWA   | : Long-term exposure limit (8-hour TWA reference period)   |
| GB EH40 / STEL  | : Short-term exposure limit (15-minute reference period)   |
| ADR             | : European Agreement concerning the International Carriage of Dangerous Goods by Road  |
| CAS             | : Chemical Abstracts Service   |
| DNEL            | : Derived no-effect level  |
| EC50            | : Half maximal effective concentration   |
| GHS             | : Globally Harmonized System   |
| IATA            | : International Air Transport Association  |
| IMDG            | : International Maritime Code for Dangerous Goods  |
| LD50            | : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50            | : Median lethal concentration (concentrations of the chemical in   |

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-292i

Date of last issue: 25.02.2021  
Revision Date: 05.07.2021

Version 9.0

Print Date 24.08.2021

|        |  |
|--------|--|
|        | air that kills 50% of the test animals during the observation period)  |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  |
| OEL    | : Occupational Exposure Limit  |
| PBT    | : Persistent, bioaccumulative and toxic  |
| PNEC   | : Predicted no effect concentration  |
| REACH  | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC   | : Substances of Very High Concern  |
| vPvB   | : Very persistent and very bioaccumulative   |

### Further information

#### Classification of the mixture:

Skin Sens. 1                      H317

#### Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

GB / EN