

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikaflex®-295 UV

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive, Product is not intended for consumer use

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
Telephone : +44 (0)1707 394444  
Telefax : +44 (0)1707 329129  
E-mail address of person : EHS@uk.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

National Chemical Emergency Centre (NCEC)  
24 Hour Emergency Telephone Number +44 870 190 6777

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H412	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b>	

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

P261	Avoid breathing mist or vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves.
<b>Response:</b>	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
<b>Disposal:</b>	
P501	Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

aliphatic prepolymer (t-polyether based)  
aliphatic prepolymer (d-polyether based)  
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate  
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate  
2-ethyl-2-[[1-(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate  
Pentamethyl piperidylsebacate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.  
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
aliphatic prepolymer (t-polyether based)	138626-39-8 Not Assigned	Skin Sens. 1; H317	>= 10 - < 20
aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>= 5 - < 10
Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72-XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	59719-67-4 261-879-6 UK-01-6693092877-6-0001	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31-XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411  specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %  Acute toxicity estimate  Acute inhalation toxicity (dust/mist): 0,031 mg/l	>= 0,25 - < 0,5

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

2-ethyl-2-[[[1-oxoallyl]oxy]methyl]-1,3-propanediyl diacrylate	15625-89-5 239-701-3 01-2119489896-11-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 0,5
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 01-2119489379-17-XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

---

If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions  
See Section 11 for more detailed information on health effects and symptoms.

Risks : sensitising effects  
May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform

---

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA (inhalable dust)	10 mg/m3	GB EH40
		TWA (Respirable dust)	4 mg/m3	GB EH40
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	GB EH40
	<p>Further information: Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even in tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance those who are likely to become hyper-responsive. Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing airway hyper-responsiveness, but which do not include the disease themselves. The latter substances are not classified as asthmagens or respiratory sensitisers. Further information can be found in the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. For substances that can cause occupational asthma, COSHH requires that exposure be reduced to as low as is reasonably practicable. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance., Capable of causing occupational asthma., The 'Sen' notation in the list of WELs has been assigned only to those substances which may cause occupational asthma in the categories shown in Table 1. It should be remembered that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (<a href="http://www.hse.gov.uk/asthma">www.hse.gov.uk/asthma</a>) provide further information.</p>			
		STEL	0,07 mg/m3 (NCO)	GB EH40

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9	isocyanate-derived diamine (Isocyanates): 1 µmol/mol creatinine (Urine)	At the end of the period of exposure	GB EH40 BAT

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	Workers	Inhalation	Long-term systemic effects	29,4 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	16,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	6,25 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	8,3 mg/kg
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate	Fresh water	0,0186 mg/l
	Marine water	0,00186 mg/l
	Fresh water sediment	0,709 mg/kg
	Marine sediment	0,0709 mg/kg
	Soil	1,131 mg/kg

## 8.2 Exposure controls

### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid  
Appearance : paste  
Colour : various  
Odour : slight

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

Method: closed cup

Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, kinematic : > 20,5 mm<sup>2</sup>/s (40 °C)

### Solubility(ies)

Water solubility : insoluble  
Partition coefficient: n-octanol/water : No data available  
Vapour pressure : 0,01 hPa  
Density : ca. 1,23 g/cm<sup>3</sup> (20 °C)  
Relative vapour density : No data available  
Particle characteristics : No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

### 10.5 Incompatible materials

Materials to avoid : No data available

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **aliphatic prepolymer (d-polyether based):**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

##### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402

##### **bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

##### **3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

##### **2-ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:**

Acute oral toxicity : LD50 Oral (Rat): 3.680 - 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **Pentamethyl piperidylsebacate:**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### SECTION 12: Ecological information

#### 12.1 Toxicity

##### Components:

##### **aliphatic prepolymer (t-polyether based):**

Toxicity to algae/aquatic plants : EC50 (algae): 100 mg/l  
Exposure time: 72 h

NOEC (algae): 100 mg/l  
Exposure time: 72 h

##### **aliphatic prepolymer (d-polyether based):**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): > 100 mg/l

NOEC (Daphnia (water flea)): > 100 mg/l

Toxicity to algae/aquatic plants : EC50 (algae): > 100 mg/l  
Exposure time: 72 h

##### **Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l  
Exposure time: 72 h

##### **bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexane-1,2-diylbiscarbamate:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 87,1 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): 18,6 mg/l  
Exposure time: 72 h

##### **2-ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,87 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

M-Factor (Acute aquatic toxicity) : 1

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

---

M-Factor (Chronic aquatic toxicity) : 1

### **Pentamethyl piperidylsebacate:**

Toxicity to fish : LC50 (Fish): 0,97 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **12.2 Persistence and degradability**

No data available

### **12.3 Bioaccumulative potential**

No data available

### **12.4 Mobility in soil**

No data available

### **12.5 Results of PBT and vPvB assessment**

#### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **12.6 Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **12.7 Other adverse effects**

#### **Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

- Product** : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue** : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances
- Contaminated packaging** : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

- ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

- ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

- ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA** : Not regulated as a dangerous good

#### 14.4 Packing group

- ADR** : Not regulated as a dangerous good  
**IMDG** : Not regulated as a dangerous good  
**IATA (Cargo)** : Not regulated as a dangerous good  
**IATA (Passenger)** : Not regulated as a dangerous good

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate (Number on list 74) m-tolidene diisocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	:	Not applicable
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 1% w/w no VOC duties



# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 1% w/w

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : Environmental Protection Act 1990 & Subsidiary Regulations  
Health and Safety at Work Act 1974 & Subsidiary Regulations  
Control of Substances Hazardous to Health Regulations (COSHH)  
May be subject to the Control of Major Accident Hazards Regulations (COMAH), and amendments.

### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 : May cause respiratory irritation.  
H351 : Suspected of causing cancer.  
H361f : Suspected of damaging fertility.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
H413 : May cause long lasting harmful effects to aquatic life.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Carc. : Carcinogenicity

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Skin Sens. 1	H317
Aquatic Chronic 3	H412

#### Classification procedure:

Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

# SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



## Sikaflex®-295 UV

Date of last issue: 13.01.2023  
Revision Date: 31.03.2023

Version 14.0

Print Date 31.03.2023

---

GB / EN