



Polyester Tape

8991/8991L

Technical Data

April, 2015

Product Description 3M™ Polyester Tape 8991 is a blue polyester tape with a silicone adhesive. It can be used in a large variety of high temperature applications including powdercoat masking, flashbreaker, and bag sealing applications. Additional applications include, splicing, tabbing, or roll closing silicone treated liners or materials.

Product Construction	Backing	Adhesive	Liner (8991L)	Color	Standard Roll Length
	Polyester	Silicone	Polyester	Blue	72 yds. (65.8 m)

Typical Physical Properties	Note: representative or typical o	ical information and data should be nly, and should not be used for specificat	ion purposes.	ASTM Test Method
Adhesion to Steel:	31 oz./in. width (34 N/100 mm)			D-3330
Tensile Strength:	29 lbs./in. width (508 N/100 mm)			D-3759
Elongation at Break:	100%			D-3759
Backing Thickness:	1.0 mils (0.025 mm) 2.4			D-3652
Total Thickness:	mils (0.061 mm)			D-3652
Liner Thickness (8991L):	3.0 mils (0.075 mm)			D-3652
Temperature Use Range:	Up to 400°F (204°C)			

- Features**
- Polyester films offer excellent thermal, abrasion, and chemical resistance while maintaining their flexibility.
 - Blue color makes tape placement obvious for both application and removal.
 - Thin backing leaves a sharp paint line and some conformability.
 - Silicone adhesives offer high heat resistance compared to many rubber and acrylic adhesives, reducing failure due to softening, oozing, and adhesive transfer.
 - Silicone adhesives adhere well to tough-to-stick-to surfaces like silicone liners and fixtures coated with mold release.
 - Silicone adhesive removes cleanly from many surfaces.
 - Lined version available for die-cuts.

Application Ideas	<ul style="list-style-type: none">• Masking for powdercoat painting.• Flashbreaker tape when pulling through cured coating such as epoxies.• Holding and splicing difficult to stick to surfaces such as silicone liner.• Holding parts or sealing vacuum bags during processing.
Storage	Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% relative humidity in the original packaging material.
Shelf Life	To obtain best performance, use this product within 24 months from date of manufacture.
Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method or application.
Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a quality system registered to ISO 9001:2000 standards.



Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 220-3S-06

St. Paul, MN 55144-1000
800-362-3550 • 577-369-2923 (Fax)
www.3M.com/industrial
G/COE/Product Technical Data Sheets/425.431.438.1433.1437

Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2015 (4/15)