



# tesa<sup>®</sup> Professional Spray Glue Extra Strong

## Product Information

BNR 60022

## Product Description

tesa<sup>®</sup> Spray Glue Extra Strong is a spray adhesive and a fabric, wood, metal and plastic glue able to firmly bond even heavy materials with rough surfaces.

## Product Features

- Suitable for heavy weight materials with rough and uneven surfaces
- Film forming spray
- Spray direction can be set either horizontal or vertical
- Adjustable spray quantity (H: high, M: medium, L: low)
- Resistant to damp and temperature from -30°C up to +80°C (short term even 100°C)
- Free from silicone

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Silicone free yes

## Properties/Performance Values

• Adhesive strength	High adhesion	• Reusable	no
• Applicationfield	Office, Home	• Solvent free	no
• Batteries included	no	• Suitable for children of 3 years of age	no
• Batteries required	no	• Suitable surfaces	Even wood, Stone, Brick, Acrylic glass
• Chemical Resistance	yes	• Temperature resistance	yes
• Compostable	no	• Temperature resistance max.	80 °C
• Ecofriendly packaging	no	• Temperature resistance min.	-30 °C
• Hazard material	yes	• UV resistant	yes
• Humidity resistance	yes	• Washable	no
• Recommended distance of spraying	30 cm	• Waterproof	yes
• Residue-free removability	no		



# tesa<sup>®</sup> Professional Spray Glue Extra Strong

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>