



VHB™ Surface Cleaner

Product Data Sheet

March 2012
Supersedes: New

Product Description

The 3M™ VHB™ Surface Cleaner consists of a mixture of isopropyl alcohol and distilled water in the ratio of 90 :10.

The 3M™ VHB™ surface cleaner can be applied on different smooth materials like metals, plastics or painted surfaces; however, compatibility should be checked beforehand.

Key Features

- Degreasing of surfaces
- Preparation of surfaces for bonding

Directions for use

Surfaces must be clean, dry and free from oil or greasy film before bonding.

Remove coarse contamination with lint-free cloth. Oxide layers can be removed with Scotch-Brite™ 7447.

Wipe surface with lint-free cloth soaked with VHB™ surface cleaner straight towards one direction until no residue is visible.

Surfaces must be dry before application of the tape. The drying time depends on environmental conditions.

Keep the container always closed and do not refill or decant into other containers. This will avoid contamination of the cleaner and evaporation of alcohol, and thus change in concentration.

Shelf Life

3M™ VHB™ Surface Cleaner has a shelf life of 24 months from date of manufacturing, when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity

Precautionary Information

Refer to product label and Material Safety Data Sheet for health and safety information before using the product.

For information please contact your local 3M Office.

www.3M.com

For Additional Information

To request additional product information or to arrange for sales assistance, please see below for contact details.

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.



**3M Svenska AB
Industri**

Bollstanäsvägen 3
191 89 Sollentuna
Tel: 08-92 21 00
Fax: 08-92 22 88
E-post:
kundservice@mmm.com
www.3M.se/tejp

**3M a/s
Industri**

Hannemanns Allé 53
2300 København S
Tlf.: 43 48 01 00
Fax.: 43 20 15 65
E-mail:
dkindustri@mmm.com
www.3Mindustri.dk

**3M Norge AS
Avd. Industri**

Hvamveien 6
2013 Skjetten
Tel: 0 63 84
Fax: 63 84 17 88
E-post:
Kundeservice@mmm.com
www.3M.no/tape

**Suomen 3M Oy
Teollisuustuotteet**

PL 600
Keilaranta 6
02151 Espoo
Puh: 09-525 21
Fax: 09-525 2279
<http://www.3M.fi/teollisuus>