

Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 35-9755-6
 Version number:
 3.01

 Revision date:
 28/01/2022
 Supersedes date:
 12/05/2021

Transportation version number: 1.00 (26/03/2019)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M(tm) Scotch-Weld(tm) 7240 B/A

Product Identification Numbers

UU-0015-6691-6

7100042087

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

32-5808-4, 35-9443-9

TRANSPORTATION INFORMATION

UU-0015-6691-6

Component 1

ADR/RID: UN3263, CORROSIVE SOLID, BASIC, ORGANIC, N.O.S., LIMITED QUANTITY, (3,3'-

3M(tm) Scotch-Weld(tm) 7240 B/A

OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8, II, (E), ADR Classification Code: C8.

IMDG-CODE: UN3263. CORROSIVE SOLID.BASIC.ORGANIC.N.O.S.. (3.3'-

OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8., II, IMDG-Code segregation code: 18- ALKALIS, LIMITED

QUANTITY, EMS: FA,SB.

ICAO/IATA: UN3263, CORROSIVE SOLID, BASIC, ORGANIC, N.O.S., (3,3'-

OXYBIS(ETHYLENEOXY)BIS(PROPYLAMINE)), 8., II.

Component 2

ADR/RID: UN3077, NOT RESTRICTED AS PER SPECIAL PROVISION 375, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXEMPTION, (EPOXY RESIN), III, --.

IMDG-CODE: UN3077, NOT RESTRICTED AS PER IMDG CODE 2.10.2.7, MARINE POLLUTANT EXCEPTION, (EPOXY RESIN), III, IMDG-Code segregation code: NONE, EMS: --.

ICAO/IATA: UN3077, NOT RESTRICTED AS PER SPECIAL PROVISION A197, ENVIRONMENTALLY

HAZARDOUS SUBSTANCE EXCEPTION, (EPOXY RESIN), III.

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |





Contains:

2-piperazin-1-ylethylamine; bis-[4-(2,3-epoxipropoxi)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); 2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated; Reaction products of fatty acids, C18-unstaturated, dimers and trimers with 3,3'-[oxybis(ethane-2,1-diyloxy)]dipropan-1-amine ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; 2,4,6-tris(dimethylaminomethyl)phenol; 2-Ethyl-4-methylimidazole

Dagge 2 of

3M(tm) Scotch-Weld(tm) 7240 B/A

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260B Do not breathe dust.

P273 Avoid release to the environment.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Kit: Component document group number(s) information was modified. Label: CLP Ingredients - kit components information was modified.

Label: CLP Classification information was modified.



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 35-9443-9 **Version number:** 3.00

Revision date: 11/05/2021 **Supersedes date:** 16/04/2020

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M(tm) Scotch-Weld(tm) 7240 B/A FR: Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Industrial use.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

 Telephone:
 +44 (0)1344 858 000

 E Mail:
 tox.uk@mmm.com

 Website:
 www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1A - Skin Sens. 1A; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400

Hazardous to the Aquatic Environment (Chronic), Category 1 - Aquatic Chronic 1; H410

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms







Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	68911-25-1		15 - 40
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	68683-29-4		10 - 30
piperazinyl)ethyl]amino]butyl-terminated			
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	7 - 13
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	5 - 10
2-Ethyl-4-methylimidazole	931-36-2	213-234-5	1 - 5
2-piperazin-1-ylethylamine	140-31-8	205-411-0	< 1

HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P260B Do not breathe dust.

P273 Avoid release to the environment.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

5% of the mixture consists of components of unknown acute dermal toxicity.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

Contains 3% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 68911-25-1	15 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 STOT SE 3, H336 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	(CAS-No.) 68683-29-4	10 - 30	Skin Irrit. 2, H315 Skin Sens. 1A, H317
Aluminium hydroxide	(CAS-No.) 21645-51-2 (EC-No.) 244-492-7 (REACH-No.) 01- 2119529246-39	10 - 30	Substance with a national occupational exposure limit
3,3'- Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2 (REACH-No.) 01- 2119963377-26	7 - 13	Skin Sens. 1, H317 Skin Corr. 1B, H314
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (REACH-No.) 01- 2119560597-27	5 - 10	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	1 - 5	Substance with a national occupational exposure limit
Nitric acid, calcium salt, tetrahydrate	(CAS-No.) 13477-34-4 (EC-No.) 233-332-1 (REACH-No.) 01- 2119495093-35	1 - 5	Acute Tox. 4, H302 Eye Dam. 1, H318
2-Ethyl-4-methylimidazole	(CAS-No.) 931-36-2 (EC-No.) 213-234-5	1 - 5	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	1 - 5	Substance with a national occupational exposure limit
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	0.5 - 1.5	Acute Tox. 4, H302 Skin Corr. 1C, H314
2-piperazin-1-ylethylamine	(CAS-No.) 140-31-8	< 1	Acute Tox. 3, H311

3M(1	m)	Scotch-V	Veld(tm	7240	B/A	FR:	Part A	١

(EC-No.) 205-411-0	Acute Tox. 4, H302
	Skin Corr. 1B, H314
	Skin Sens. 1B, H317
	Aquatic Chronic 3, H412
	Repr. 2, H361d
	STOT RE 1, H372

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Amine compounds. Carbon monoxide

Condition

During combustion.

During combustion.

Carbon dioxide.
Oxides of nitrogen.

During combustion. During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
DUST, INERT OR NUISANCE	21645-51-2	UK HSC	TWA(as respirable dust):4	
			mg/m3;TWA(as inhalable	
			dust):10 mg/m3	
Glass, oxide, chemicals	65997-17-3	UK HSC	TWA(as fiber):5 mg/m3(1	
			fibers/ml)	

3M(tm) Scotch-Weld(tm) 7240 B/A FR : Part A

Oxide glass chemicals 65997-17-3 Manufacturer TWA(as non-fibrous,

determined respirable)(8 hours):3

mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10

mg/m3

Silicon dioxide 67762-90-7 UK HSC TWA(as respirable dust):2.4

mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation	Population	Human exposure	DNEL
	Product		pattern	
2,4,6-		Worker	Inhalation, Long-term	0.31 mg/m^3
tris(dimethylaminomethyl)			exposure (8 hours),	
phenol			Systemic effects	

Predicted no effect concentrations (PNEC)

Ingredient	Degradation	Compartment	PNEC
	Product		
2,4,6-		Freshwater	0.084 mg/l
tris(dimethylaminomethyl)			
phenol			
2,4,6-		Intermittent releases to water	0.84 mg/l
tris(dimethylaminomethyl)			
phenol			
2,4,6-		Marine water	0.0084 mg/l
tris(dimethylaminomethyl)			
phenol			
2,4,6-		Sewage Treatment Plant	0.2 mg/l
tris(dimethylaminomethyl)			
phenol			

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield. Indirect vented goggles.

Applicable Norms/Standards
Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolid.Specific Physical Form:PasteColourOff-WhiteOdorAmine

Odour thresholdNo data available.Melting point/freezing pointNo data available.Boiling point/boiling rangeNo data available.Flammability (solid, gas)Not classifiedFlammable Limits(LEL)Not applicable.Flammable Limits(UEL)Not applicable.Flash point>=100 °C

Autoignition temperature

No data available.

Decomposition temperature

No data available.

3M(tm) Scotch-Weld(tm) 7240 B/A FR : Part A

pН

Kinematic Viscosity

80.36 mm²/sec

Water solubility

No data available.

Solubility- non-water

No data available.

No data available.

Vapour pressure

Not applicable.

No data available.

Not applicable.

No data available.

Relative density 1.12 [*Ref Std:* WATER=1]

Relative Vapor Density *Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rat	LD50 > 2,000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 > 2,000 mg/kg
Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Dermal	Rabbit	LD50 > 3,000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	Ingestion	Rat	LD50 > 15,300 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,500 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 3,160 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
2-Ethyl-4-methylimidazole	Ingestion	Rat	LD50 681 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar	LD50 > 2,000 mg/kg
		compoun ds	

Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Bis[(dimethylamino)methyl]phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
2-piperazin-1-ylethylamine	Dermal	Rabbit	LD50 865 mg/kg
2-piperazin-1-ylethylamine	Ingestion	Rat	LD50 1,470 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
		¥ 4.
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	Rat	Irritant
oxybis(ethyleneoxy)bis(propylamine)	1	
Aluminium hydroxide	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	Rabbit	Irritant
piperazinyl)ethyl]amino]butyl-terminated		
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
2-Ethyl-4-methylimidazole	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	similar	No significant irritation
	compoun	
	ds	
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Bis[(dimethylamino)methyl]phenol	similar	Corrosive
	compoun	
	ds	
2-piperazin-1-ylethylamine	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
The state of the s	1	
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	In vitro	Severe irritant
oxybis(ethyleneoxy)bis(propylamine)	data	
Aluminium hydroxide	Rabbit	No significant irritation
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	Rabbit	Mild irritant
piperazinyl)ethyl]amino]butyl-terminated		
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	similar	Corrosive
	health	
	hazards	
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive
2-Ethyl-4-methylimidazole	Rabbit	Corrosive
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Bis[(dimethylamino)methyl]phenol	similar	Corrosive
	compoun	
	ds	
2-piperazin-1-ylethylamine	Rabbit	Corrosive

Skin Sensitisation

Name	Species Value

Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	Guinea	Sensitising
oxybis(ethyleneoxy)bis(propylamine)	pig	_
Aluminium hydroxide	Guinea	Not classified
	pig	
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	Guinea	Sensitising
piperazinyl)ethyl]amino]butyl-terminated	pig	
2,4,6-tris(dimethylaminomethyl)phenol	Guinea	Not classified
	pig	
2-Ethyl-4-methylimidazole	Mouse	Sensitising
Nitric acid, calcium salt, tetrahydrate	similar	Not classified
	compoun	
	ds	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
2-piperazin-1-ylethylamine	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-	In Vitro	Not mutagenic
oxybis(ethyleneoxy)bis(propylamine)	III VIIIO	Not mutageme
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic
2-Ethyl-4-methylimidazole	In Vitro	Not mutagenic
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
2-piperazin-1-ylethylamine	In vivo	Not mutagenic
2-piperazin-1-ylethylamine	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium hydroxide	Not	Multiple	Not carcinogenic
	specified.	animal	
		species	
Oxide glass chemicals	Inhalation	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
Siloxanes and Silicones, di-Me, reaction products with silica	Not	Mouse	Some positive data exist, but the data are not
	specified.		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis

Dagge 11 of 2

2-Ethyl-4-methylimidazole	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	premating into lactation
2-Ethyl-4-methylimidazole	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	29 days
2-Ethyl-4-methylimidazole	Ingestion	Not classified for development	Rat	NOAEL 230 mg/kg/day	during gestation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-piperazin-1-ylethylamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
2-piperazin-1-ylethylamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
2-piperazin-1-ylethylamine	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
2-Propenenitrile, polymer with 1,3-butadiene, 1- cyano-1-methyl-4-oxo-4- [[2-(1- piperazinyl)ethyl]amino]bu tyl-terminated	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2,4,6- tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Ethyl-4-methylimidazole	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemi a	Causes damage to organs	Human	NOAEL Not available	environmental exposure
2-piperazin-1-ylethylamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for		NOAEL Not available	

	classification		
	Classification		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
2-Ethyl-4-methylimidazole	Ingestion	heart hematopoietic system liver kidney and/or bladder respiratory system skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes vascular system	Not classified	Rat	NOAEL 230 mg/kg/day	90 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2-piperazin-1-ylethylamine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
2-piperazin-1-ylethylamine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m3	13 weeks
2-piperazin-1-ylethylamine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 53.8 mg/m3	13 weeks

3M(tm) Scotch-Weld(tm) 7240 B/A FR : Part A

system		mg/kg/day	
hematopoietic			
system liver			
nervous system			
kidney and/or			
bladder			

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis (propylamine)	68911-25-1	Fathead minnow	Experimental	96 hours	LL50	2.16 mg/l
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis (propylamine)	68911-25-1	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis (propylamine)	68911-25-1	Water flea	Experimental	48 hours	EL50	0.57 mg/l
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis (propylamine)	68911-25-1	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis (propylamine)	68911-25-1	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
2-Propenenitrile, polymer with 1,3- butadiene, 1-cyano-1- methyl-4-oxo-4-[[2-(1- piperazinyl)ethyl]amino]butyl-terminated	68683-29-4		Data not available or insufficient for classification			N/A
Aluminium hydroxide	21645-51-2	Fish other	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l

Aluminium hydroxide	21645-51-2	Green Algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green Algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
3,3'- Oxybis(ethyleneoxy)bis (propylamine)	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
3,3'- Oxybis(ethyleneoxy)bis (propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'- Oxybis(ethyleneoxy)bis	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
(propylamine) 3,3'- Oxybis(ethyleneoxy)bis	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
(propylamine) 3,3'- Oxybis(ethyleneoxy)bis	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
(propylamine) 2,4,6- tris(dimethylaminometh yl)phenol	90-72-2		Experimental	96 hours	LC50	718 mg/l
	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6- tris(dimethylaminometh yl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6- tris(dimethylaminometh yl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6- tris(dimethylaminometh yl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
	931-36-2	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
2-Ethyl-4- methylimidazole	931-36-2	Golden Orfe	Experimental	96 hours	LC50	68.1 mg/l
2-Ethyl-4- methylimidazole	931-36-2	Green algae	Experimental	72 hours	EC50	124.8 mg/l
2-Ethyl-4- methylimidazole	931-36-2	Water flea	Experimental	48 hours	EC50	297.3 mg/l
2-Ethyl-4- methylimidazole	931-36-2	Green algae	Experimental	72 hours	NOEC	31.25 mg/l
	13477-34-4	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		Data not available or insufficient for classification			N/A
Bis[(dimethylamino)me thyl]phenol	71074-89-0		Data not available or insufficient for classification			NA
2-piperazin-1- ylethylamine	140-31-8	Bacteria	Experimental	17 hours	EC10	100 mg/l

2-piperazin-1-	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
ylethylamine						
2-piperazin-1-	140-31-8	Green Algae	Experimental	72 hours	EC50	>1,000 mg/l
ylethylamine						
2-piperazin-1-	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
ylethylamine						
2-piperazin-1-	140-31-8	Green Algae	Experimental	72 hours	NOEC	31 mg/l
ylethylamine						

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	68911-25-1	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301F - Manometric respirometry
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]but yl-terminated	68683-29-4	Data not availblinsufficient			N/A	
Aluminium hydroxide	21645-51-2	Data not availbl- insufficient			N/A	
3,3'- Oxybis(ethyleneoxy)bis(pro pylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	Non-standard method
3,3'- Oxybis(ethyleneoxy)bis(pro pylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
2,4,6- tris(dimethylaminomethyl)p henol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % BOD/ThBOD	OECD 301D - Closed bottle test
2-Ethyl-4-methylimidazole	931-36-2	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	86 %removal of DOC	OECD 301A - DOC Die Away Test
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not availbl- insufficient			N/A	
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient			N/A	
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient			N/A	
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Biodegradation	28 days	BOD	41 %CO2 evolution/THC O2 evolution	Catalogic™
2-piperazin-1-ylethylamine	140-31-8	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	68911-25-1	Modeled Bioconcentration		Bioaccumulation factor	42	Catalogic [™]
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	68911-25-1	Modeled Bioconcentration		Log Kow	11.7	Episuite™
2-Propenenitrile, polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

piperazinyl)ethyl]amino]bu tyl-terminated						
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3,3'- Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	Non-standard method
2,4,6- tris(dimethylaminomethyl) phenol	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	830.7550 Part.Coef Shake Flask
2-Ethyl-4-methylimidazole	931-36-2	Experimental Bioconcentration		Log Kow	1.13	Non-standard method
Nitric acid, calcium salt, tetrahydrate	13477-34-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis[(dimethylamino)methyl]phenol	71074-89-0	Modeled Bioconcentration		Log Kow	-2.34	ACD/Labs ChemSketch™
2-piperazin-1-ylethylamine	140-31-8	Experimental Bioconcentration		Log Kow	0.3	Non-standard method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Fatty acids, C18- unsaturated, dimers, polymers with 3,3'- oxybis(ethyleneoxy)bis(pro pylamine)	68911-25-1	Modeled Mobility in Soil	Koc	3 l/kg	
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	4246-51-9	Modeled Mobility in Soil		ERROR: Length cannot be greater than the length of the string.	ACD/Labs ChemSketch™
2-Ethyl-4-methylimidazole	931-36-2	Estimated Mobility in Soil	Koc	90 l/kg	Episuite TM

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical

substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

IATA: UN3263; Corrosive Solid, Basic, Organic, N.O.S. (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II. IMDG: UN3263; Corrosive Solid, Basic, Organic, N.O.S. (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II; EMS: FA, SB.

ADR: UN3263; Corrosive Solid, Basic, Organic, N.O.S (3,3'-Oxybis(Ethyleneoxy)Bis(Propylamine)); 8; II; (E); C8.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

EU Section 09: pH information information was added.

Formulation: Section 16: Annex information was modified.

Industrial Use of Adhesives: Section 16: Annex information was modified.

Professional Mixing and Application: Section 16: Annex information was modified.

CLP: Ingredient table information was modified.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was added.

Label: CLP Percent Unknown information was added.

Label: CLP Percent Unknown information was deleted.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Label: Graphic information was modified.

Section 03: Composition table % Column heading information was added.

Section 3: Composition/Information of ingredients table information was modified.

Section 03: Substance not applicable information was added.

Section 04: First Aid - Symptoms and Effects (CLP) information was added.

Section 04: Information on toxicological effects information was modified.

Section 5: Hazardous combustion products table information was added.

Section 6: Accidental release clean-up information information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Precautions safe handling information information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 9: Evaporation Rate information information was deleted.

Section 9: Explosive properties information information was deleted.

Section 09: Kinematic Viscosity information information was added.

Section 9: Melting point information information was modified.

Section 9: Oxidising properties information information was deleted.

Section 9: pH information information was deleted.

Section 9: Property description for optional properties information was modified.

Section 9: Vapour density value information was added.

Section 9: Vapour density value information was deleted.

Section 9: Viscosity information information was deleted.

Section 10: Hazardous decomposition products during combustion text information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Classification disclaimer information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: No endocrine disruptor information available warning information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Reproductive/developmental effects information information was added.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: 12.6. Endocrine Disrupting Properties information was added.

Section 12: 12.7. Other adverse effects information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Contact manufacturer for more detail. information was deleted.

Section 12: Mobility in soil information information was added.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14 Classification Code – Main Heading information was added.

- Section 14 Classification Code Regulation Data information was added.
- Section 14 Control Temperature Main Heading information was added.
- Section 14 Control Temperature Regulation Data information was added.
- Section 14 Disclaimer Information information was added.
- Section 14 Emergency Temperature Main Heading information was added.
- Section 14 Emergency Temperature Regulation Data information was added.
- Section 14 Hazard Class + Sub Risk Main Heading information was added.
- Section 14 Hazard Class + Sub Risk Regulation Data information was added.
- Section 14 Hazardous/Not Hazardous for Transportation information was added.
- Section 14 Multiplier Main Heading information was added.
- Section 14 Multiplier Regulation Data information was added.
- Section 14 Other Dangerous Goods Main Heading information was added.
- Section 14 Other Dangerous Goods Regulation Data information was added.
- Section 14 Packing Group Main Heading information was added.
- Section 14 Packing Group Regulation Data information was added.
- Section 14 Proper Shipping Name information was added.
- Section 14 Regulations Main Headings information was added.
- Section 14 Segregation Regulation Data information was added.
- Section 14 Segregation Code Main Heading information was added.
- Section 14 Special Precautions Main Heading information was added.
- Section 14 Special Precautions Regulation Data information was added.
- Section 14 Transport Category Main Heading information was added.
- Section 14 Transport Category Regulation Data information was added.
- Section 14 Transport in bulk Regulation Data information was added.
- Section 14 Transport in bulk according to Annex II of Marpol and the IBC Code Main Heading information was added.
- Section 14 Transport Not Permitted Main Heading information was added.
- Section 14 Transport Not Permitted Regulation Data information was added.
- Section 14 Tunnel Code Main Heading information was added.
- Section 14 Tunnel Code Regulation Data information was added.
- Section 14 UN Number Column data information was added.
- Section 14 UN Number information was added.
- Section 14: Transportation classification information was modified.
- Section 15: Carcinogenicity information information was deleted.
- Section 15: Regulations Inventories information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Annex

1. Title	
Substance identification	2,4,6-tris(dimethylaminomethyl)phenol; EC No. 202-013-9; CAS Nbr 90-72-2;
Exposure Scenario Name	Formulation
Lifecycle Stage	Formulation or re-packing
Contributing activities	PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
Processes, tasks and activities covered	Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs. Transfers with dedicated controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk mana	gement measures
Operating Conditions	Physical state:Liquid.

Page: 20 of 22

	General operating conditions: Air exchange rate:: >= 3 times per hour; Indoor use; Partially open and partially closed process; Processing Temperature: <= 40 degree Calcium			
	Processing Temperature:: <= 40 degree Celsius; Task: PROC08b; Duration of exposure per day at workplace [for one worker]: 8 hours/day;			
	Task: PROC09; Duration of exposure per day at workplace [for one worker]: <= 4 hour(s);			
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: Local exhaust ventilation; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Environmental: None needed;			
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:			
3. Prediction of exposure				
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.			

1. Title	
Substance identification	2,4,6-tris(dimethylaminomethyl)phenol;
	EC No. 202-013-9;
	CAS Nbr 90-72-2;
Exposure Scenario Name	Industrial Use of Adhesives
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 05 -Mixing or blending in batch processes
	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-
	dedicated facilities
	PROC 10 -Roller application or brushing
	PROC 13 -Treatment of articles by dipping and pouring
	ERC 05 -Use at industrial site leading to inclusion into/onto article
Processes, tasks and activities covered	Application of product with a roller or brush. Application of product with
	applicator gun. Mixing operations (open systems). Transfers without dedicated
	controls, including loading, filling, dumping, bagging.
2. Operational conditions and risk mana	agement measures
Operating Conditions	Physical state:Liquid.
* *	General operating conditions:
	Air exchange rate:: >= 3 times per hour;
	Duration of exposure per day at workplace [for one worker]: <= 4 hour(s);
	Indoor use;
	Processing Temperature:: <= 40 degree Celsius;
	T. I. PDOCOS
	Task: PROC05;
D' I	Duration of exposure per day at workplace [for one worker]: 8 hours/day;
Risk management measures	Under the operational conditions described above the following risk management
	measures apply:
	General risk management measures:
	Human health:
	Local exhaust ventilation;
	Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for
	specific glove material.;

	Environmental: None needed;
Waste management measures	Do not release to waterways or sewers;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

Г	
1. Title	
Substance identification	2,4,6-tris(dimethylaminomethyl)phenol;
	EC No. 202-013-9;
	CAS Nbr 90-72-2;
Exposure Scenario Name	Hand-mixing of preparations, e.g. plasters, resins, two-component adhesives.
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 10 -Roller application or brushing
	ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
Processes, tasks and activities covered	Application of product.
2. Operational conditions and risk mana	ngement measures
Operating Conditions	Physical state:Liquid.
	General operating conditions:
	Duration of exposure per day at workplace [for one worker]: 8 hours/day;
	Indoor use;
	Processing Temperature:: <= 40 degree Celsius;
Risk management measures	Under the operational conditions described above the following risk management
_	measures apply:
	General risk management measures:
	Human health:
	Local exhaust ventilation;
	Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for
	specific glove material.;
	Environmental:
	None needed;
Waste management measures	Do not release directly to waterways;
-	
3. Prediction of exposure	I .
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and
	PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 32-5808-4 **Version number:** 6.04

Revision date: 11/05/2021 **Supersedes date:** 16/07/2020

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3MTM Scotch-WeldTM 7240 B/A FR- Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

 Telephone:
 +44 (0)1344 858 000

 E Mail:
 tox.uk@mmm.com

 Website:
 www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1A - Skin Sens. 1A; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols

GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms





Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	14228-73-0	238-098-4	< 30
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	10 - 30
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	500-006-8	10 - 30
STANNOUS SULFATE	7488-55-3	231-302-2	< 1

HAZARD STATEMENTS:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

15% of the mixture consists of components of unknown acute oral toxicity.

Contains 16% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	(CAS-No.) 14228-73-0 (EC-No.) 238-098-4	< 30	Aquatic Chronic 3, H412 Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5 (REACH-No.) 01- 2119456619-26	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Aluminium hydroxide	(CAS-No.) 21645-51-2 (EC-No.) 244-492-7 (REACH-No.) 01- 2119529246-39	10 - 30	Substance with a national occupational exposure limit
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-No.) 01- 2119454392-40	10 - 30	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Oxide glass chemicals	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	< 20	Substance with a national occupational exposure limit
Acrylic copolymer	Trade Secret	< 10	Substance not classified as hazardous
OXIDE GLASS CHEMICALS (non-fibrous)	(CAS-No.) 65997-17-3 (EC-No.) 266-046-0	3 - 7	Substance with a national occupational exposure limit
Silicon dioxide	(CAS-No.) 7631-86-9 (EC-No.) 231-545-4 (REACH-No.) 01- 2119379499-16	< 5	Substance with a national occupational exposure limit
red phosphorus	(CAS-No.) 7723-14-0 (EC-No.) 918-594-3 (REACH-No.) 01- 2119489913-23	< 3	Flam. Sol. 1, H228 Aquatic Chronic 3, H412
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01- 2119513212-58	< 3	Eye Dam. 1, H318
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	< 3	Substance with a national occupational exposure limit
STANNOUS SULFATE	(CAS-No.) 7488-55-3 (EC-No.) 231-302-2	< 1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8 (EC-No.) 219-784-2 (REACH-No.) 01- 2119513212-58	(C >= 5%) Eye Dam. 1, H318
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

on.
on.
on.
on.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Store in a well-ventilated place. Store away from heat. Store away from acids. Store away from strong bases.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
DUST, INERT OR NUISANCE	21645-51-2	UK HSC	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Glass, oxide, chemicals	65997-17-3	UK HSC	TWA(as fiber):5 mg/m3(1 fibers/ml)	
Oxide glass chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous,	

			inhalable fraction)(8 hours):10 mg/m3
Silicon dioxide	67762-90-7	UK HSC	TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable
			dust):6 mg/m3
TIN, INORGANIC	7488-55-3	UK HSC	TWA(as Sn):2
COMPOUNDS, EXCEPT SnH4			mg/m3;STEL(as Sn):4 mg/m3
Silicon dioxide	7631-86-9	UK HSC	TWA(as respirable dust):2.4
			mg/m3;TWA(as inhalable
			dust):6 mg/m3
red phosphorus	7723-14-0	UK HSC	TWA: 0.1 mg/m ³ ; STEL: 0.3
1 1			mg/m³

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use with appropriate local exhaust ventilation.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Applicable Norms/Standards
Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid.

Specific Physical Form:

Thixotropic paste

ColourBlackOdorMild EpoxyOdour thresholdNo data available.Melting point/freezing pointNo data available.

Boiling point/boiling rangeNot applicable.Flammability (solid, gas)Not classifiedFlammable Limits(LEL)Not applicable.Flammable Limits(UEL)Not applicable.

Flash point >=100 °C [Test Method:Closed Cup]

Autoignition temperature Decomposition temperatureNot applicable.

No data available.

pН

Kinematic Viscosity 67.30769 - 181.818181 mm²/sec

Water solubilityNo data available.Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNot applicable.

DensityNot applicable.
1.04 - 1.1 g/cm3

Relative density 1.04 - 1.1 [Ref Std:WATER=1]

Relative Vapor Density *Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Percent volatile1 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

3MTM Scotch-WeldTM 7240 B/A FR- Part B

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Strong acids.

Strong bases.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Aluminium hydroxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium hydroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Dermal	Rabbit	LD50 > 2,000 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 1.7 mg/l
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Ingestion	Rat	LD50 > 5,000 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Rat	LD50 1,098 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
OXIDE GLASS CHEMICALS (non-fibrous)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
red phosphorus	Dermal		LD50 estimated to be > 5,000 mg/kg
red phosphorus	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.1 mg/l
red phosphorus	Ingestion	Rat	LD50 > 15,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
STANNOUS SULFATE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 2 mg/l
STANNOUS SULFATE	Ingestion	Rat	LD50 2,207 mg/kg
STANNOUS SULFATE	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
ATE - conta tanicita actimata	-1	iiii.ai ab	1

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Skii Collosion/Illitation		
Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Aluminium hydroxide	Rabbit	No significant irritation
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and	Rabbit	Mild irritant
phenol		

Decay O of 10

1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro	Irritant
	data	
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgemen	
	t	
OXIDE GLASS CHEMICALS (non-fibrous)	Professio	No significant irritation
	nal	
	judgemen	
	t	
Silicon dioxide	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
STANNOUS SULFATE	Professio	Irritant
	nal	
	judgemen	
	t	

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Aluminium hydroxide	Rabbit	No significant irritation
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Rabbit	No significant irritation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vitro data	No significant irritation
Oxide glass chemicals	Professio nal judgemen t	No significant irritation
OXIDE GLASS CHEMICALS (non-fibrous)	Professio nal judgemen t	No significant irritation
Silicon dioxide	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
STANNOUS SULFATE	Professio nal judgemen t	Corrosive

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Aluminium hydroxide	Guinea	Not classified
	pig	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and	Multiple	Sensitising
phenol	animal	
	species	
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Mouse	Sensitising
Silicon dioxide	Human	Not classified
	and	
	animal	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea	Not classified
	pig	
STANNOUS SULFATE	Human	Sensitising

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In vivo	Not mutagenic
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
STANNOUS SULFATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium hydroxide	Not specified.	Multiple animal species	Not carcinogenic
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Aluminium hydroxide	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	33 days
1,4-Bis[(2,3-epoxypropoxy)methyl]cyclohexane	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497	1 generation

				mg/kg/day	
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3- epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
1,4-Bis[(2,3-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
epoxypropoxy)methyl]cycl			data are not sufficient for	health	available	
ohexane			classification	hazards		
STANNOUS SULFATE	Inhalation	respiratory irritation	May cause respiratory irritation	Professio	NOAEL Not	
				nal	available	
				judgeme		
				nt		

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
1,4-Bis[(2,3- epoxypropoxy)methyl]cycl ohexane	Ingestion	endocrine system gastrointestinal tract liver heart hematopoietic system immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 300 mg/kg/day	33 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3- epoxypropoxy)propyl]trim	Ingestion	heart endocrine system bone, teeth,	Not classified	Rat	NOAEL 1,000	28 days

D 10 C 1

ethoxysilane		nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system			mg/kg/day	
STANNOUS SULFATE	Ingestion	hematopoietic system liver heart kidney and/or bladder	Not classified	Rat	NOAEL 40 mg/kg/day	4 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Bacteria	Estimated	18 hours	EC50	10,264 mg/l
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Green algae	Estimated	72 hours	EC50	26.7 mg/l
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Rainbow trout	Estimated	96 hours	LC50	10.1 mg/l
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Water flea	Estimated	48 hours	EC50	16.3 mg/l
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Green algae	Estimated	72 hours	EC10	21.4 mg/l
1,4-Bis[(2,3- epoxypropoxy)methyl]c yclohexane	14228-73-0	Water flea	Estimated	21 days	NOEC	11.7 mg/l
Aluminium hydroxide	21645-51-2	Fish other	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green Algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Aluminium hydroxide	21645-51-2	Green Algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l

bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
		<u> </u>		0.61	T 0.50	<u> </u>
bis-[4-(2,3- epoxipropoxi)phenyl]pr opane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phenyl]pr	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
opane						
bis-[4-(2,3-	1675-54-3	Green Algae	Experimental	72 hours	EC50	>11 mg/l
epoxipropoxi)phenyl]pr opane	1073 34 3	Green Angue	Ехрегиненци	72 Hours	Leso	r II mg/I
bis-[4-(2,3-	1675-54-3	Green Algae	Experimental	72 hours	NOEC	4.2 mg/l
epoxipropoxi)phenyl]pr opane	1070 013	oreen riigue	Z.ip v. i.i.v.	, 2 nours		2
bis-[4-(2,3-	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
epoxipropoxi)phenyl]pr opane		, attack from	Z.ip v. i.i.v.	21 days		l mg i
Formaldehyde,	9003-36-5	Green Algae	Experimental	72 hours	EC50	1.8 mg/l
oligomeric reaction			1			
products with 1-chloro- 2,3-epoxypropane and						
phenol						
Formaldehyde,	9003-36-5	Activated sludge	Unknown	3	IC50	>100 mg/l
oligomeric reaction						
products with 1-chloro-						
2,3-epoxypropane and						
phenol						
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide glass chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
OXIDE GLASS	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
CHEMICALS (non-fibrous)						
OXIDE GLASS	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
CHEMICALS (non-			•			
fibrous)						
OXIDE GLASS	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
CHEMICALS (non-fibrous)	00997 17 5		г. Генераличина Г) o nound		1,000 mg/
OXIDE GLASS	65997-17-3	Green algae	Experimental	72 hours	NOEC	>1,000 mg/l
CHEMICALS (non-fibrous)	03777-17-3	Green argae	Experimental	72 hours	NOLC	7,000 mg/1
Silicon dioxide	7631-86-9		Data not available		İ	N/A
	, , , ,		or insufficient for classification			
[3-(2,3-	2530-83-8	Bacteria	Experimental	5 hours	EC10	1,520 mg/l
epoxypropoxy)propyl]tr						-,
imethoxysilane					[
[3-(2,3-	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
epoxypropoxy)propyl]tr		Common Carp	Laperinicitai	>0 Hould	1200	55 mg/1
imethoxysilane						
[3-(2,3-	2530-83-8	Crustacea other	Experimental	48 hours	LC50	324 mg/l
		Crustacea other	Experimental	46 Hours	LC30	324 mg/1
epoxypropoxy)propyl]tr imethoxysilane						
[3-(2,3-	2530-83-8	Green algae	Experimental	96 hours	EC50	350 mg/l
epoxypropoxy)propyl]tr imethoxysilane						
[3-(2,3-	2530-83-8	Green Algae	Experimental	96 hours	NOEC	130 mg/l
epoxypropoxy)propyl]tr imethoxysilane		B	r			
[3-(2,3-	2530-83-8	Water flea	Experimental	21 days	NOEC	>=100 mg/l
epoxypropoxy)propyl]tr		ater freu	Z.iperimentui	2. 44,5		100 mg/1

Page: 14 of 19

imethoxysilane						
red phosphorus	7723-14-0	Activated sludge	Estimated	3 hours	NOEC	1,000 mg/l
red phosphorus	7723-14-0	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
red phosphorus	7723-14-0	Green algae	Experimental	72 hours	EL50	18.3 mg/l
red phosphorus	7723-14-0	Water flea	Experimental	48 hours	EL50	10.5 mg/l
red phosphorus	7723-14-0	Zebra Fish	Experimental	96 hours	EL50	2.5 mg/l
red phosphorus	7723-14-0	Green algae	Experimental	72 hours	EL10	6.6 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		Data not available or insufficient for classification			N/A
STANNOUS SULFATE	7488-55-3	Activated sludge	Experimental	3 hours	EC50	1,194 mg/l
STANNOUS SULFATE	7488-55-3	Diatom	Laboratory	72 hours	EC50	0.2 mg/l
STANNOUS SULFATE	7488-55-3	Water flea	Laboratory	48 hours	EC50	39.08 mg/l
STANNOUS SULFATE	7488-55-3	Zebra Fish	Laboratory	120 hours	NOEC	9.48 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
1,4-Bis[(2,3- epoxypropoxy)methyl]cyclo hexane	14228-73-0	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	16.6 %removal of DOC	OECD 301F - Manometric respirometry
Aluminium hydroxide	21645-51-2	Data not availbl- insufficient			N/A	
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	Non-standard method
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	Experimental Biodegradation	28 days	CO2 evolution	16 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Oxide glass chemicals	65997-17-3	Data not availbl- insufficient			N/A	
OXIDE GLASS CHEMICALS (non-fibrous)	65997-17-3	Data not availbl- insufficient			N/A	
Silicon dioxide	7631-86-9	Data not availbl- insufficient			N/A	
[3-(2,3- epoxypropoxy)propyl]trimet hoxysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life	6.5 hours (t 1/2)	Non-standard method
[3-(2,3-epoxypropoxy)propyl]trimet hoxysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 % weight	Non-standard method
red phosphorus	7723-14-0	Experimental Hydrolysis		Hydrolytic half-life	8.3 years (t 1/2)	Non-standard method
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not availbl- insufficient			N/A	
STANNOUS SULFATE	7488-55-3	Data not availbl- insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
1,4-Bis[(2,3- epoxypropoxy)methyl]cycl ohexane	14228-73-0	Estimated Bioconcentration		Bioaccumulation factor	3	Estimated: Bioconcentration factor
Aluminium hydroxide	21645-51-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
bis-[4-(2,3- epoxipropoxi)phenyl]propa ne	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	Non-standard method
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	Experimental Bioconcentration		Log Kow	≤3.6	OECD 117 log Kow HPLC method
Oxide glass chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
OXIDE GLASS CHEMICALS (non- fibrous)	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3- epoxypropoxy)propyl]trime thoxysilane	2530-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
red phosphorus	7723-14-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
STANNOUS SULFATE	7488-55-3	Estimated BCF - Other	1 days	Bioaccumulation factor	3000	Non-standard method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
1,4-Bis[(2,3-epoxypropoxy)methyl]cycl ohexane	14228-73-0	Estimated Mobility in Soil	Koc	57 l/kg	Episuite TM
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5	Experimental Mobility in Soil	Koc	4,460 l/kg	OECD 121 Estim. of Koc by HPLC
[3-(2,3- epoxypropoxy)propyl]trime thoxysilane	2530-83-8	Estimated Mobility in Soil	Koc	58 l/kg	Episuite TM

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

IMDG: UN3077; Environmentally Hazardous Substance, Solid, N.O.S (Solid Epoxy Resin); 9; III; Marine Pollutant: Solid Epoxy Resin; EMS: FA, SF.

Exemption: For vessels containing a net quantity of 5 l or a net mass of 5 kg or less per single or inner packaging, special provision 375 (ADR), exemption per 2.10.2.7 (IMDG) or special provision A197 (IATA) may be applied, if applicable ADR: UN3077; Environmentally Hazardous Substance, Solid, N.O.S (Solid Epoxy Resin); 9; III; (-); M7. IATA: UN3077; Environmentally Hazardous Substance, Solid, N.O.S (Solid Epoxy Resin); 9; III.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	CAS Nbr	<u>Classification</u>	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency
			for Research on Cancer
Silicon dioxide	7631-86-9	Gr. 3: Not classifiable	International Agency
			for Research on Cancer

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

EU Section 09: pH information information was added.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Disposal information was deleted.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Section 03: Composition table % Column heading information was added.

Section 3: Composition/Information of ingredients table information was modified.

Section 03: SCL table information was added.

Section 03: Substance not applicable information was added.

Section 04: Information on toxicological effects information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 9: Density information information was modified.

Section 9: Evaporation Rate information information was deleted.

Section 9: Explosive properties information information was deleted.

Section 09: Kinematic Viscosity information information was added.

Section 9: Melting point information information was modified.

Section 9: Oxidising properties information information was deleted.

Section 9: pH information information was deleted.

Section 9: Property description for optional properties information was modified.

Section 9: Vapour density value information was added.

Section 9: Vapour density value information was deleted.

Section 9: Viscosity information information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Classification disclaimer information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: No endocrine disruptor information available warning information was added.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: 12.6. Endocrine Disrupting Properties information was added.

Section 12: 12.7. Other adverse effects information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Contact manufacturer for more detail, information was deleted.

Section 12: Mobility in soil information information was added.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: Persistence and Degradability information information was modified.

- Section 12:Bioccumulative potential information information was modified.
- Section 14 Classification Code Main Heading information was added.
- Section 14 Classification Code Regulation Data information was added.
- Section 14 Control Temperature Main Heading information was added.
- Section 14 Control Temperature Regulation Data information was added.
- Section 14 Disclaimer Information information was added.
- Section 14 Emergency Temperature Main Heading information was added.
- Section 14 Emergency Temperature Regulation Data information was added.
- Section 14 Hazard Class + Sub Risk Main Heading information was added.
- Section 14 Hazard Class + Sub Risk Regulation Data information was added.
- Section 14 Hazardous/Not Hazardous for Transportation information was added.
- Section 14 Multiplier Main Heading information was added.
- Section 14 Multiplier Regulation Data information was added.
- Section 14 Other Dangerous Goods Main Heading information was added.
- Section 14 Other Dangerous Goods Regulation Data information was added.
- Section 14 Packing Group Main Heading information was added.
- Section 14 Packing Group Regulation Data information was added.
- Section 14 Proper Shipping Name information was added.
- Section 14 Regulations Main Headings information was added.
- Section 14 Segregation Regulation Data information was added.
- Section 14 Segregation Code Main Heading information was added.
- Section 14 Special Precautions Main Heading information was added.
- Section 14 Special Precautions Regulation Data information was added.
- Section 14 Transport Category Main Heading information was added.
- Section 14 Transport Category Regulation Data information was added.
- Section 14 Transport in bulk Regulation Data information was added.
- Section 14 Transport in bulk according to Annex II of Marpol and the IBC Code Main Heading information was added.
- Section 14 Transport Not Permitted Main Heading information was added.
- Section 14 Transport Not Permitted Regulation Data information was added.
- Section 14 Tunnel Code Main Heading information was added.
- Section 14 Tunnel Code Regulation Data information was added.
- Section 14 UN Number Column data information was added.
- Section 14 UN Number information was added.
- Section 14: Transportation classification information was modified.
- Section 15: Carcinogenicity information information was modified.
- Section 15: Regulations Inventories information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk