




# tesa<sup>®</sup> 55576

## Product Information



1200 µm double sided PE foam tape

## Product Description

tesa<sup>®</sup> 55576 is a double sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive, covered with a red film liner.

## Product Features

tesa<sup>®</sup> 55576 is a double sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive, covered with a red film liner.

## Application Fields

- Trims & Profiles Mounting
- POS Signs & Advertising Material Mounting
- Mirror Pre-Mounting
- Temporary Mounting
- Gap Filling

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Properties/Performance Values

- |                                    |       |                                     |       |
|------------------------------------|-------|-------------------------------------|-------|
| • Static shear resistance at 40°C  | low   | • Temperature resistance short term | 80 °C |
| • Temperature resistance long term | 60 °C |                                     |       |

## Adhesion to Values

- |                       |          |                   |          |
|-----------------------|----------|-------------------|----------|
| • Aluminium (initial) | 6.4 N/cm | • PVC (initial)   | 3 N/cm   |
| • PE (initial)        | 1.4 N/cm | • Steel (initial) | 5.5 N/cm |



# tesa<sup>®</sup> 55576

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=55576>